

MasterTig 235ACDC GM AU



OVERVIEW

230 A AC/DC, 1-phase generator and multi-voltage use, VRD locked on

TECHNICAL SPECIFICATIONS

MasterTig 235ACDC GM AU

Product code	MT235ACDCGMAU
Connection voltage 1~ 50/60 Hz	110 / 240 V ±10 %
Fuse	15 A
Stick electrode sizes	1.6...5.0 mm
Recommended generator power (min)	8 kVA
Open circuit voltage (average)	23 V (locked to VRD)
Operating temperature range	-20...+40 °C
External dimensions LxWxH	544 x 205 x 443 mm
Weight (no accessories)	19.1 kg
Degree of protection	IP23S
Standards	IEC 60974-1,-3,-10 IEC 61000-3-12 AS 60974.1-2006 GB 15579.1
EMC class	A
Rated maximum output at 40 °C (240 V) 40 % TIG	230 A / 19.2 V
Rated maximum output at 40 °C (240 V) 60 % TIG	200 A / 18 V
Rated maximum output at 40 °C (240 V) 100 % TIG	170 A / 16.8 V
Rated maximum output at 40 °C (240 V) 37 % MMA	180 A / 27.2 V
Rated maximum output at 40 °C (240 V) 60 % MMA	150 A / 26 V

MasterTig 235ACDC GM AU

Rated maximum output at 40 °C (240 V) 100 % MMA	120 A / 24.8 V
Rated maximum output at 40 °C (110 V) 40 % TIG	130 A / 15.2 V
Rated maximum output at 40 °C (110 V) 60 % TIG	110 A / 14.4 V
Rated maximum output at 40 °C (110 V) 100 % TIG	90 A / 13.6 V
Rated maximum output at 40 °C (110 V) 40 % MMA	85 A / 23.4 V
Rated maximum output at 40 °C (110 V) 60 % MMA	75 A / 23 V
Rated maximum output at 40 °C (110 V) 100 % MMA	55 A / 22.2 V
Range of output (110 V) TIG	3 A / 1 V ... 130 A / 24 V
Range of output (240 V) TIG	3 A / 1 V ... 230 A / 31 V
Range of output (110 V) MMA	10 A / 1 V ... 85 A / 35 V
Range of output (240 V) MMA	10 A / 10 V ... 180 A / 40 V